



7K

Size (Diagonal): 17" (43.2cm), Dot Pitch: 0.21mm(H), 0.25mm(D), Pure Flat

16.0" (40.6cm)

300mm x 230mm

Video: 0.7Vp-p, RGB Analog, Separate Sync: TTL Level, H/V Sync: Positive/Negative

VESA, SXGA, XGA, SVGA, VGA, Mac® Equipped With VGA Port

Horizontal: 30K~95KHz, Vertical: 50~160Hz

200MHz

1600 x 1200@75Hz

8

20

Universal 100~240VAC, 50/60Hz

120 Watts (Max)

Yes

RGB Signal: 15-Pin D-sub Male (Attached)

Power: 3-Pin Plug (CEE22)

OSD Shuttle Knob, Standby Power Key

Contrast, Brightness, H-Size, H-Center, V-Size, V-Center, Zoom, Pincushion, Trapezoid, Pin-balance, Parallelogram, Rotation, 6500K, 9300K, User's Color, Degauss, H/V Moire Reduce, Recall, Language, Exit

VESA DDC1/2B

Teo 92

UL, FCC, FDA, CSA, TUV/GS

Ivory, Black, Silver / Black

Note: Specifications subject to change without notice.



9K

Size (Diagonal): 19" (48.3cm), Dot Pitch: 0.21mm(H) Mask, 0.25mm(D) Mask FST

18.0" (45.7cm)

346mm x 260mm

Video: 0.7Vp-p, RGB Analog, Separate Sync: TTL Level, H/V Sync: Positive/Negative

VESA, UXGA, SXGA, XGA, SVGA, VGA, Mac® Equipped With VGA Port

Horizontal: 30K~95KHz, Vertical: 50~160Hz

200MHz

1600 x 1200@75Hz

8

20

Universal 100~240VAC, 50/60Hz

150 Watts (Max)

Yes

RGB Signal: 15-Pin D-sub Male (Attached)

Power: 3-Pin Plug (CEE22)

OSD Shuttle Knob, Standby Power Key

Contrast, Brightness, H-Size, H-Center, V-Size, V-Center, Zoom, Pincushion, Trapezoid, Pin-balance, Parallelogram, Rotation, 6500K, 9300K, User's Color, Degauss, H/V Moire Reduce, Recall, Language, Exit

VESA DDC1/2B

TC092

UL, FCC, FDA, CSA, TUV/GS

vory, Black, Silver / Black

Note: Specifications subject to change without notice.



## LM729

TFT Active Matrix LCD, Slim Cabinet, VIS: 17" (43.2cm), Diagonal

0.2805mm x 0.2805mm

359mm x 287mm

300 cd/m2

450:1

25ms

Horizontal: 150 Degrees, Vertical: 125 Degrees

VESA, SXGA, XGA, SVGA, VGA, Mac® Equipped With VGA Port

Horizontal: 30K~80KHz, Vertical: 55~75Hz

135MHz

1280 x 1024@75Hz

1280 x 1024@60Hz

16.7M

Video: 0.7Vp-p, RGB Analog, Separate Sync: TTL Level, H/V Sync: Positive/Negative

RGB Signal: 15-Pin D-sub Male (Attached), Dvi-D: 24-Pin Dvi-D Power: Coax Power Jack

DVI, Speaker, Pivot, Height Adjustment USB

DC Input: 12VDC 3.5A

Power Adapter Input: Universal 100~240VAC, 50/60Hz

Power Adapter Output: 12VDC 5A (Max)

50 Watts (Max)

DDC1/2B

Yes

Auto Adjust, Left Key, Right Key, Menu Key, On/Off Key

Brightness, Contrast, Focus, Clock, H/V Position, Auto Center, Language, DOS Mode, C1(7300), C2(8300), Recall, Exit, RGB

English, French, German, Spanish and Italian

TCO92/TCO95/TCO99

UL, CSA, FCC, TUV/GS, CE, ISO 13406-2, Windows® XP Logo, Tco99

VESA 100mm Wall Mountable\*, Kensington Security Slot

Note: Specifications subject to change without notice.

\*Wall mount arm and bracket not included.



## LM929

TFT Active Matrix LCD Slim Cabinet, VIS: 19" (48cm): Diagonal Hard Coating (3H), Anti-glare Treatment

0.294mm x 0.294mm

376mm x 301mm

250 cd/m2

600:1

25ms

Horizontal: 170 Degrees, Vertical: 170 Degrees

VESA, SXGA, XGA, SVGA, VGA, Mac® Equipped With VGA Port

Horizontal: 24K~93KHz, Vertical: 55~85Hz

80MHz(Analog)24K~83K(Dvi-D)

1280 x 1024@85Hz(Analog), 1280 x 1024@75Hz(Dvi-D)

1280 x 1024@60Hz

16.7M

Video: 0.7Vp-p, RGB Analog, Separate Sync: TTL Level, H/V Sync: Positive/Negative

RGB Signal: 15-Pin D-sub Male (Attached), Dvi-D: 24-Pin Dvi-D Power: Coax Power Jack

DVI, Speaker, Pivot, Height Adjustment USB

DC Input: 12VDC 5A

Power Adapter Input: Universal 100~240VAC, 50/60Hz

Power Adapter Output: 12VDC 5A (Max)

60 Watts (Max)

DDC1/2B

Yes

Auto Adjust, Left Key, Right Key, Menu Key, On/Off Key

Brightness, Contrast, Focus, Clock, H/V Position, Auto Center, Language, DOS Mode, C1(7300), C2(8300), Recall, Exit, RGB

English, French, German, Spanish and Italian

TCO99

UL, FCC, TUV/GS, CE

VESA 100mm Wall Mountable,\*Kensington Security Lock, V-chip,Closed Caption

Note: Specifications subject to change without notice.

\*Wall mount arm and bracket not included.



## LM520

Panel TFT Active Matrix LCD, Slim Cabinet, VIS: 15" (38.1cm), Diagonal

Pixel Pitch	0.297mm x 0.297mm
Display Area	304mm x 228mm
Brightness	250 cd/m2
Contrast Ratio	400:1
Response Time	25ms
Viewing Angle	Horizontal: 120 Degrees, Vertical: 110 Degrees
Compatibility	VESA, XGA, SVGA, VGA, Mac <sup>®</sup> Equipped With VGA Port
Scanning Frequency	Horizontal: 30K~60KHz, Vertical: 55~75Hz
Pixel Frequency	80MHz
Maximum Resolution	1024 x 768@75Hz
Recommended Resolution	1024 x 768@60Hz
Color	16.7M
Signal Input	Video: 0.7Vp-p, RGB Analog, Separate Sync: TTL Level, H/V Sync: Positive/Negative
Connectors	RGB Signal: 15-Pin D-sub Male (Attached) Power: Coax Power Jack
<b>Speakers</b>	
Power Source	DC Input: 12VDC 2.5A Power Adapter Input: Universal 100~240VAC, 50/60Hz Power Adapter Output: 12VDC 5A (Max)
Power Consumption	25 Watts (Max)
Plug & Play	DDC1/2B
EPA ENERGY STAR <sup>®</sup>	Yes
User Control	Auto
OSD Functions	Brightness, Contrast, Focus, Clock, H/V Position, Language, Color Temperature (C1, C2), Reset, Exit, RGB
Emissions Standard	TCO92/TCO95/TCO99
Regulations	UL, CSA, FCC, TUV/GS, CE, ISO 13406-2, Windows <sup>®</sup> XP Logo
Other Features	VESA 75mm Wall Mountable*, Kensington Security Slot

Note: Specifications subject to change without notice.  
\*Wall mount arm and bracket not included.



## SE

CRT Size (Diagonal): 15" (38.1cm), Dot Pitch: 0.28mm, FST

Viewable Image Size (Diagonal)	13.8" (35cm)
Preset Display Area	260mm x 195mm
Signal Input	Video: 0.7Vp-p, RGB Analog, Separate Sync: TTL Level, H/V Sync: Positive/Negative
Compatibility	VESA, XGA, SVGA, VGA
Scanning Frequency	Horizontal: 30K~54KHz, Vertical: 50~120Hz
Pixel Frequency	65MHz
Maximum Resolution	1024 x 768 @60Hz
Factory Preset Mode	5
User Programmable Mode	12
Power Source	Universal 100~254VAC, 50/60Hz
Power Consumption	75 Watts (Max)
EPA ENERGY STAR <sup>®</sup>	Yes
Connectors	15-Pin Mini D-sub Male (Attached)
Front Panel Controls	Power Switch, Function Key, up/down key
OSD Functions	Contrast, Brightness, H-Size, H-Center, V-Size, V-Center, Pincushion, Trapezoid, Rotation, Recall, Volume Up/Down
<b>Speaker Base</b>	
Plug & Play	VESA DDC1/2B
Emissions Standard	
Regulations	UL, FCC, FDA, CSA, TUV/GS, CE
Cabinet Color Option	Ivory, Black, Silver / black

Note: Specifications subject to change without notice.